

# ANJI YIKE DECORATION MATERIAL TECHNOLOGY CO., LTD

# **TEST REPORT**

#### **SCOPE OF WORK**

Woven vinyl flooring

#### **REPORT NUMBER**

191106006SHF-003

#### **TEST DATE(S)**

2019-11-06 - 2019-11-21

#### **ISSUE DATE**


2019-11-21

#### **PAGES**

5

#### **DOCUMENT CONTROL NUMBER**

LFT-APAC-SHF-OP-10k(May 1, 2019) © 2019 INTERTEK



Intertek Testing Services Shenzhen Ltd. Shanghai Fengxian Branch



Intertek Testing Services Shenzhen Ltd. Shanghai Fengxian Branch
Plant 5, No. 6958 Daye Road, Fengxian District, Shanghai, China
Tel: 021-61136116 Fax: 021-61189921

Website: www.intertek.com

## **Test Report**

### **Statement**

- 1. This report is invalid without company's special seal for testing on assigned page.
- 2. This report is invalid without authorized person's signature.
- 3. This report is invalid where any unauthorized modification indicated.
- 4.Don't copy this report in partial (except full copy) without any official approval in written by our company. This report is invalid without re-stamping the special seal for testing in copying report.

5.Any holder of this document is advised that this report is for the exclusive use of Intertek's Customer and is provided pursuant to the agreement between Intertek and its Customer. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. This report was made with due care within the limitation of a defined scope of work and on the basis of information, materials and instructions received from the Customer or its nominated third parties. Intertek is under no obligation to refer to or report upon any facts or circumstances which are outside the specific instructions received and accepts no responsibility to any parties whatsoever, following the issue of the report, for any matters arising outside the agreed scope of the works. The tests results are not intended to be a recommendation for any particular course of action. Customer is responsible for acting as it sees fit on the basis of such results.

6.Intertek's written consent is required to use Intertek's name or logo on the object, product or service being tested. The observations and test results in this report relate only to the sample under test. This report alone does not indicate that the item, product or service has passed any Intertek certification program.

Version: 1 May 2019 Page 2 of 5 LFT-APAC-SHF-OP-10k



Intertek Testing Services Shenzhen Ltd. Shanghai Fengxian Branch Plant 5, No. 6958 Daye Road, Fengxian District, Shanghai, China Tel: 021-61136116 Fax: 021-61189921

Website: www.intertek.com

# **Test Report**

Issue Date: 2019-11-21 Intertek Report No. 191106006SHF-003

Applicant: ANJI YIKE DECORATION MATERIAL TECHNOLOGY CO., LTD

Address: BUILDING 1, BAMBOO INDUSTRYTECHNOLOGY ENTREPRENEURSHIP CENTER XIAOFENG TOWN,

ANJI COUNTY, HUZHOU CITY, ZHEJIANG PROVINCE, CHINA

Attn: Juanny

Test Type: Performance test, samples provided by the applicant.

#### **Product Information**

<b>Product Name</b>		Woven vinyl flooring	Brand	ECO BEAUTY
Sample		Good Condition	Sample Amount	1 PC
Description		Good Condition	Received Date	2019-11-06
Sample ID		Model	Specification	
S191106006SHF.003		ECO	/	

#### **Test Methods And Standards**

Test Standard	EN 985:2001 Test C
Specification Standard	
Test Conclusion	The samples were tested according to the above standards, and the results are shown in the following page.

#### Note:

1. This report relates specifically to the sample(s) that were drawn and provided by the applicant or their nominated third party. The reported result(s) provide no warranty or verification on the sample(s) representing any specific goods and/or shipment and only relate to the sample(s) as received and tested.

**Report Authorized** 

Name: Mason Wang

Title: Reviewer

Version: 1 May 2019

Jackie Zhou

roject Engineer

Name

Page 3 of 5



# **Test Report**

Issue Date: 2019-11-21 Intertek Report No. 191106006SHF-003

#### Test Items, Method and Results:

Test Item: Castor chair test
Test Method: EN 985:2001 Test C

Conditioning: Condition the test specimens at  $(23 \pm 2)^{\circ}$ C and  $(50 \pm 5)\%$  relative humidity for at least 24h

Test Condition: At a temperature range of 18°C to 25 °C

Load mass:90kgTest castors:TypeWSpeed of rotating platform:20r/minSpeed of castor assembly:50r/minTotal test revolutions:25000r


Mounting of the specimen: Floating installation with click joints

#### Test Result:

Type of damage	Observation (Yes/No)	Verdict
Loosening, swelling or tearing of the covering	No	
Delamination	No	
Flaking or delamination of foam backin	No	Pass
Loss of cohesion and lor powdering of binder	No	
Any destruction of the material as a whole	No	

#### Test Photos:







After 25000r



# **Test Report**

Issue Date: 2019-11-21 Intertek Report No. 191106006SHF-003

#### **Appendix A: Sample Received Photo**



#### **Revision:**

NO.	Date	Changes	Author	Reviewer
191106006SHF-003	2019-11-21	First issue	Jackie Zhou	Mason Wang