

ANJI YIKE DECORATION MATERIAL TECHNOLOGY CO., LTD

ZHUYI RD, TANGPU INDUSTRIAL ZONE, ANJI COUNTY, ZHEJIANG PROVINCE CHINA

THE TEST REPORT IS TO SUPERSEDE THE TEST REPORT No.: AJD201406301, DATE: AUG.12, 2014

The following sample(s) was / were submitted and identified on behalf of the client as:

Sample Description: WOVEN VINYL FLOOR COVERING**Style/Item No.:** ECO**Supplier:** ANJI YIKE DECORATION MATERIAL TECHNOLOGY CO., LTD**Manufacturer:** ANJI YIKE DECORATION MATERIAL TECHNOLOGY CO., LTD**Country of Origin:** CHINA**Test Requested:**EN 13501-1:2007+A1:2009 Fire classification of construction products and building elements—Part 1:
Classification using data from reaction to fire tests, Class B_{fl}**Test Results:** -- See attached sheet --**Test Period:**

Sample Receiving Date : JUL.25, 2014

Test Performing Date : JUL.25, 2014 TO AUG.11, 2014

Signed for and on behalf of
SGS-CSTC Co., Ltd.Allen Zou
Technical Manager

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, jurisdiction and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its issuance only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all the rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

I. Test conducted

This test was conducted as per EN 13501-1:2007+A1:2009 Fire classification of construction products and building elements — Part 1: Classification using data from reaction to fire tests. And the test methods as following:

1. EN ISO 9239-1:2010 Reaction to fire tests for floorings —Part 1: Determination of the burning behaviour using a radiant heat source.
2. EN ISO 11925-2:2010 Reaction to fire tests — Ignitability of building products subjected to direct impingement of flame — Part 2: Single-flame source test.

II. Details of classified product

Description

Mass per unit area	About 3.3kg/m ²
--------------------	----------------------------

Mounting and fixing:

Fire cement board, with its density approximate 1800kg/m³, thickness approximate 6mm, is as the substrate. The test specimens are fixed mechanically to the substrate with no cavity behind it.

III. Test results

Test method	Parameter	Number of tests	Results
EN ISO 9239-1	Critical flux (kW/m ²)	3	9.35
	Smoke (%×minutes)		207.6
EN ISO 11925-2 Exposure = 15 s	<i>F_s</i> ≤ 150 mm	6	YES

To be continued...

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, jurisdiction and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its issue for information only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



IV. Classification and direct field of application

This classification has been carried out in accordance with **EN 13501-1:2007**.

a) Classification

The product, WOVEN VINYL FLOOR COVERING, classification is as following,

Fire behaviour		Smoke production	
B _{fl}	—	s	1

Reaction to fire classification: B_{fl}—S1

Remark: The classes with their corresponding fire performance are given in annex A.

b) Field of application

This classification for the submitted sample is valid for the following end use condition:

- With all substrates classified A1 and A2
- With mechanical fixing

This classification is valid for the following product parameters:

- Characteristics of specimen as described in § II of this test report

Statement: The test results relate to the behaviour of the test specimens of a product under the particular conditions of the test; they are not intended to be the sole criterion for assessing the potential fire hazard of the product in use.

Warning:

This classification report does not represent type approval or certification of the product.

The test laboratory has, therefore, play no part in sampling the product for the test, although it holds appropriate references to the manufacturer’s factory production control that is aimed to be relevant to the samples tested and that will provide for their traceability.

To be continued...

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, jurisdiction and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its issue and is valid only within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Annex A

Classes of reaction to fire performance for floorings

class	Test methods	Classification	Additional classification
A _{1fi}	EN ISO 1182 ^a and	$\Delta T \leq 30^\circ\text{C}$, $\Delta m \leq 50\%$, $t_f = 0$ (i.e. no sustained flaming)	-
	EN ISO 1716	PCS $\leq 2.0\text{MJ/kg}$ ^a PCS $\leq 2.0\text{MJ/kg}$ ^b PCS $\leq 1.4\text{MJ/m}^2$ ^c PCS $\leq 2.0\text{MJ/kg}$ ^d	-
A _{2fi}	EN ISO 1182 ^a or	$\Delta T \leq 50^\circ\text{C}$, $\Delta m \leq 50\%$, $t_f \leq 20\text{s}$	-
	EN ISO 1716	PCS $\leq 3.0\text{MJ/kg}$ ^a PCS $\leq 4.0\text{MJ/m}^2$ ^b PCS $\leq 4.0\text{MJ/m}^2$ ^c PCS $\leq 3.0\text{MJ/kg}$ ^d	-
	EN ISO 9239-1 ^e	Critical flux ^f $\geq 8.0\text{kW/m}^2$	Smoke productio ^g
B _{fi}	EN ISO 9239-1 ^e and	Critical flux ^f $\geq 8.0\text{kW/m}^2$	Smoke productio ^g
	EN ISO 11925-2 ^h Exposure = 15s	F _s $\leq 150\text{mm}$ within 20 s	-
C _{fi}	EN ISO 9239-1 ^e and	Critical flux ^f $\geq 4.5\text{kW/m}^2$	Smoke productio ^g
	EN ISO 11925-2 ^h Exposure = 15s	F _s $\leq 150\text{mm}$ within 20 s	-
D _{fi}	EN ISO 9239-1 ^e and	Critical flux ^f $\geq 3.0\text{kW/m}^2$	Smoke productio ^g
	EN ISO 11925-2 ^h Exposure = 15s	F _s $\leq 150\text{mm}$ within 20 s	-
E _{fi}	EN ISO 11925-2 ^h Exposure = 15s	F _s $\leq 150\text{mm}$ within 20 s	-
F _{fi}	No performance determined		

^a For homogeneous products and substantial components of non-homogeneous products.
^b For any external non-substantial component of non-homogeneous products.
^c For any internal non-substantial component of non-homogeneous products.
^d For the product as a whole.
^e Test duration = 30 min.
^f Critical flux is defined as the radiant flux at which the flame extinguishes or the radiant flux after a test period of 30 min, whichever is the lower (i.e. the flux corresponding with the furthest extent of spread of flame).
^g s1 = Smoke ≤ 750 % minutes;
s2 = not s1.
^h Under conditions of surface flame attack and, if appropriate to the end use application of the product, edge flame attack.

To be continued...

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, jurisdiction and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its issuance only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise indicated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Photo Appendix:



End of Report

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, jurisdiction and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its issuance only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.